



Index

No.	Description	Remarks	Q'ty
1.	Outer Cover	Flame Retardant Resin	1
2.	Main Unit		1
3.	Terminal Screws	M3	4
4.	LED Indicator	Yellow	1

Specifications

SLC Applied Voltage	: Rated range 20 to 38 VDC
SLC Current Consumption	: Standby 100 μ A Activated (SCI Isolation) 22mA
LED Visual Indicator	: SCI LED (Yellow)
Applicable Electrical Box	: 4 inch Square box
Applicable Standard	: UL864
UL Ambient Installation Temperature	: 0 $^{\circ}$ C (32 $^{\circ}$ F) to +49 $^{\circ}$ C (120 $^{\circ}$ F)
Operating Temperature	: -10 $^{\circ}$ C (14 $^{\circ}$ F) to +55 $^{\circ}$ C (131 $^{\circ}$ F)
Storage Temperature	: -20 $^{\circ}$ C (-4 $^{\circ}$ F) to +60 $^{\circ}$ C (140 $^{\circ}$ F)
Maximum Relative Humidity Environment	: Up to 93%RH, non-condensing : Indoor dry use only

NITTAN COMPANY, LIMITED			
SCALE	1 / 2	DATE	Dec. 01, 2016
MODEL NO.	EVA-SCI		
TITLE	Short Circuit Isolator Module		
DRAWING NO.	N0100019	Dim:	mm