



Index

No.	Description	Remarks	Q'ty
1.	Main Body	Flame Retardant Resin	1
2.	Hatch		2
3.	Terminal Plate		5
4.	Terminal Screw	M4	5
5.	Sound Outlet		1
6.	Locking Screw	Hexagon setscrew M3	1
7.	Label		1

Specifications

SLC Applied Voltage	: Rated Range 20VDC to 38VDC
AUX. Supply Voltage	: Rated Range 16VDC to 33VDC
SLC Current Consumption	: Standby 0.5mA Alarm 1.4mA
AUX. Current Consumption	: Standby 0.5mA Alarm 20mA
Sound Pressure Level	: Over 85dB at 10ft away
Wire Size	: AWG 12-20
Applicable Standard	: UL521, UL268, UL464
UL Ambient Installation Temperature	: 0°C (32°F) to +38°C (100°F)
Operating Temperature	: -10°C (14°F) to +55°C (131°F)
Storage Temperature	: -20°C (-4°F) to +60°C (140°F)
Maximum Relative Humidity	: Up to 95%RH, non-condensing
Environment	: Indoor dry use only

NITAN COMPANY, LIMITED	
SCALE	1 / 2 DATE Dec. 01, 2016
MODEL NO.	EVA-S6 Base
TITLE Addressable Sounder Base	
DRAWING NO.	N0100006 Dim: mm